

Item: 20201



finish

gloss 230

finish & sealer
self polishing & leveling
23% metal cross-linked polymer

CHEMCOR
CHEMICAL CORP
CHINO, CA 91710
CHEMCORCHEMICAL.COM

NET 1 GAL. (3.78L)
glosa superior cera del suelo

WARNING

Keep out of reach of children.
May cause irritation to eyes and skin.
May be harmful if swallowed.

finish gloss 230

institutional & commercial high solids floor finish

DESCRIPTION

This is a 23%, high solids metal cross-linked, all acrylic copolymer floor finish that produces a very durable and tough continuous film. Dries to a clear, hard "wet look" gloss that is resistant to heavy traffic, scuff and black heel marks without buffing. Combines outstanding anti-slip properties, detergent resistance and easy recoatability in a finish that levels perfectly and dries quickly between coats. Non-yellowing, resists powdering and is spray buffable for periodic restorability. May be used on most types of floor surfaces, including vinyl, vinyl composition, asphalt tile, linoleum, sealed concrete, terrazzo, quarry tile and many others.

DIRECTIONS

A properly maintained floor is essential for long lasting performance and beauty.

Application

Remove all excess soil with a concentrated cleaner. Floors with heavy finish build-up, remove with a strong stripper. Rinse and let dry. If floor is porous, seal with a quality sealer as per directions. Apply 2 to 3 thin uniform coats of floor finish. Allow each coat to dry thoroughly between applications. Approximately 30 minutes dry time per coat.

Daily Maintenance

Frequent dust mopping and daily damp mopping with a neutral cleaner.
May be sprayed-buffed or uhs burnished.

WARNING

Keep out of reach of children.

May be harmful if swallowed. May cause irritation to eyes and skin.

Avoid prolonged or repeated breathing of vapor or spray mists.

Protect eyes, skin and mucous membranes from contact with this product and its' use solutions.

May cause irritation to the respiratory tract. Wear rubber gloves and goggles or face shield.

FIRST AID

Eyes: In case of contact, immediately flush thoroughly with plenty of cool running water. Remove contact lenses if worn. Continue flushing for at least 15 minutes holding eyelids apart. If irritation persists, get medical attention promptly. **Ingestion:** If swallowed, do not induce vomiting. Rinse mouth. Immediately drink 1 to 2 glasses of water or milk. Never give anything by mouth to an unconscious person. **Call a physician or poison control center immediately.** **Skin:** In case of contact, immediately flush thoroughly with plenty of cool running water for at least 15 minutes. Immediately remove contaminated clothing and shoes. Wash prior to reuse. **Inhalation:** If discomfort is experienced from exposure to mist or spray, the person should employ respiratory protection or leave the contaminated area until proper ventilation is restored. Breath fresh air. If irritation persists, get medical attention.

Manufacturer: Chemcor Chemical Corp. - 13770 Benson Avenue, Chino, CA 91710

Toll Free: 1-877-243-6267 / **Local:** 1-909-590-7234 / www.chemcorchemical.com

Ingredients: water: (CAS: 7732-18-5) / styrene acrylic copolymer: (CAS: 25085-34-1).

Refer to product SDS for additional information.

Before discarding container, rinse with water.

For institutional and commercial use.

DESCRIPCIÓN

This is a 23%, high solids metal cross-linked, all acrylic copolymer floor finish that produces a very durable and tough continuous film. Dries to a clear, hard "wet look" gloss that is resistant to heavy traffic, scuff and black heel marks without buffing. Combines outstanding anti-slip properties, detergent resistance and easy recoatability in a finish that levels perfectly and dries quickly between coats. Non-yellowing, resists powdering and is spray buffable for periodic restorability. May be used on most types of floor surfaces, including vinyl, vinyl composition, asphalt tile, linoleum, sealed concrete, terrazzo, quarry tile and many others.

INSTRUCCIONES PARA USO

Un propiamente mantenido piso está esencial por ejecución larga duradera y belleza.

Aplicación

Remueva toda suciedad excedente con un limpiador concentrado. Pisos con un aumento pesado del cera, remuevase con un cera-quitador fuerte. Enjuague y dejase secar.

Si el piso está poroso, sellase con un sellador bueno según instrucciones.

Aplique 2 a 3 cubiertas delgadas semejantes de cera del piso.

Deje que cada cubierta a secar completamente en medio aplicaciones.

Aproximadamente 30 minutos secando tiempo por cubierta.

Mantenimiento Diario

Frecuente polvo trapeando y diario mojado trapeando con un limpiador del neutral.
Rocie-pulido o uhs día brillo.

ADVERTENCIA

Mantenga lejos del alcance de niños.

Puede causar irritación de los ojos y piel. Puede estar fatal si tragado.

Evite prolongado o repetido respiración de vapores o rocíese lloviznas.

Proteja los ojos, piel y membranas mucosas de contacto con este producto y sus soluciones usadas.

Puede causar irritación del tracto respiratorio. Lleve guantes del caucho, gafas protectoras o escudo de la cara.

TRATAMIENTOS PRÁCTICOS

Ojos: En caso de contacto inmediatamente enjuaguese completamente con una abundancia de agua fresca. Remueva contacto-lentes si llevado. Continúe enjuagando por lo menos 15 minutos manteniendo párpados aparte. Si irritación persiste, obtengase atención médica rápidamente.

Ingestión: Si tragado, no induzca vomitando. Enjuague boca. Inmediatamente bebase 1 a 2 vasos de agua o leche. Nunca des cualquier cosa a boca a una persona inconsciente. **Llame un médico o centro de la autoridad de la ponzoña inmediatamente.** **Piel:** En caso de contacto inmediatamente enjuaguese completamente con una abundancia de agua fresca por lo menos 15 minutos. Inmediatamente remuevase contaminado ropa y zapatos. Laves prior a usando otra vez.

Inhalación: Si experimentando incomodidad de exposición a la llovizna o rocío, la persona deberá emplear protección respiratoria o salgas el contaminado área hasta que ventilación apropiado es restaurado. Respire aire fresco. Si irritación persiste, obtengase atención médica.

Consulte la SDS del producto

para obtener información adicional.

Antes de descargar el contenedor,

enjuague con agua.

Para uso institucional y comercial.

